

CONTI AIR® STEEL CDG

Coldset Printing Blanket



CONTI AIR® STEEL CDG

The metalback blanket developed for waterless Newspaper Printing.

- Designed for waterless Newspaper presses
- Optimized for waterless inks
- Developed for highest durabilty
- > Hard/medium blanket construction
- > Reduced ink build up and linting
- > High resistance to edge cutting
- > Using the special CONTIAIR® microcell technology


Guiding Value

		Standard
Application:	Waterless Coldset	
Nominal Thickness:	1.95 - 2.00 mm (According to Manufacturers Drawing)	DIN EN ISO 2286-3*
True Rolling (Paper feed characteristics):	slightly positive	
Color:	dark gray	
Surface finish:	ground	
Hardness of Surface Compound (shore A):	65	DIN ISO 48-4:2021-02*/**
Metal base:	Stainless Steel	
Backside:	Calibrated Film	

^{*} Performed in accordance with the given standard. Please note that the procedure of testing could be deviate and that the number of samples tested may differ

Unsere Drucktücher verfügen über eine spezielle CONTI-AIR® kompressible Schicht geschlossener Mikrozellen mit Überdruck.

Our printing blankets have a special CONTI-AIR® compressible layer of over pressured microcells.







ContiTech Elastomer-Beschichtungen GmbH

Breslauer Str. 14 | 37154 Northeim | Germany service@contiair.com www.contiair.com



Der Inhalt dieser Druckschrift ist unverbindlich und dient ausschließlich Informationszwecken. Für weitere Information besuchen Sie bitte: www.continental-industry.com/discl_de



^{*} The specified hardness of the cover compound can only be measured using test samples according to the standard. It is not possible to measure the hardness directly on the product itself.